

Dexxo Optimo RTS

GARAGE DOORS MOTORIZATION



- Can be supplied by a solar panel or by stand-alone battery
- 1 button per function : total opening, partial opening, light
- Easy addition of new remote controls
- partial opening mode for lateral sectional doors (80 cm opening)

Optimised solution : you need to tailor your solution to each individual customer's need.

- **Reliability tested:** tested for over 36 500 cycles for residential use.



- Up and running in **90 seconds**.
- **Simple and immediate** programming.

TECHNICAL CHARACTERISTICS

Mains power supply	230 V - 50 Hz
Motor power supply	24 Vdc
Max. power consumption in operation	120 W
Max. power consumption on standby	4 W
Traction force - peak force	800 N
Max. no. of operations/day	20 (standard rail)
Max. speed	14 cm/s
Operating temperature	-20° C / +60° C
Somfy radio frequency	RTS 433.42 MHz
Number of channels that can be memorised	32
Weight per pack	6 kg
Pack dimensions	L 470, H 230, I 210
Tested for	36,500 cycles (standard rail)

PACK

COMFORT AND SAFETY ACCESSORIES



	Dexxo Optimo RTS motor	Keytis ^{RS} 2 RTS ref. 1841026	RTS wall-mounted control unit ref. 1841027	Photoelectric cells ref. 9014994	24 V amber light ref. 9015171	Backup battery ref. 9001001	RTS Radio Keypad Metal France - ref. 1841111 International - ref. 1841116	Radio Safety Kit for side door ref. 1822285	Mechanical Lock ref. 9015607	Packs per pallet
Dexxo Optimo ref. 1216127	●	● (2x)	-	-	-	-	-	-	-	30
Dexxo Optimo ref. 1216195	●	● (2x)	-	-	-	-	-	-	-	30

*Mounting set including: 1 arm for connection to door, 1 door block, 1 hinged lintel block, 4 ceiling brackets, screws and fittings.